



98.00 EUR

incl. 19% VAT, plus shipping

- Motorized Pan/Tilt!
- Motorized Zoom!
- POE!
- Web Interface !

Support: Installation

CTFCAM-1 is an IP-camera with PTZ-support (control camera head left/right, up/down via software) and motorized zoom (control zoom 2.8-12mm via software). The camera is powered via POE-LAN-connector. The camera has a web interface for playback/recording/configuration. She also can be connected to ONVIF compatible video recorders and/or be controlled by ONVIF compatible software.

Specifications:

Image Sensor 1080P: Hi3516C + 1/3" SC2035

Max. Pixels 1920*1080P S/N Ratio 50dB(AGC Off)

LEDs & IR View 4*High Power LED make max 80m IR distance, built in IR-CUT

Lens 4x Optical zoom, (f=2.8-12mm) motorized zoom, Auto Focus

White Balance Auto, ATW, Indoor, Outdoor, Outdoor Auto, Sodium Vapor Lamp Fix/Auto, One-push, Manual

Min. Illumination (F1.6,50IRE, ICR Off), 0.095 lux (F1.6,50IRE, ICR On)

Day & Night Auto(ICR) / Color / B/W Video Compression H.264/MJPEG

S/N Ratio > 50 dB

Bit Rate 64K~8Mbps

Electronic Shutter 1/1-1/10000s

PTZ Mode 4 auto scan, 4 tour, 4 pattern

Network Functions TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPOE/DDNS/NFS/ RTSP

Max Remote Users 128

Operating System Embedded Linux

Pan / Tilt Range Pan: 0°~260, Tilt: -5°~60, Speed: 12°/sec

Preset 256 Preset (Camera Image Setting)

Protocol PELCO-P, PELCO-D

Working Humidity 0~95%(No condensation)
Working Temperature Outdoor: -35°C~+60°C

Power Supply: POE

Resource Simultaneous remote monitoring, remote operation & local recording