



129.00 EUR

incl. 19% VAT, plus [shipping](#)

- 2x Gigabit LAN !
- 6x COM port !
- 12VDC Input !
- Mini-PCI Express !



Remnant offer. Refurbished. 2 years warranty.

- INTEL® Cedar Trail-D Processor D2550 + NM10 Chipset
- Support 2 * DDR3 800/1067MHz Single CH up to 4GB
- Support DirectX 9 Graphics
- Support 2 * Serial ATAII (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- 1 * 24 bits Single Channel LVDS header
- Supports 2 * Realtek RT8111EVL Gigabit LAN
- Support 6 * COM ports (COM2 for RS232/422/485)
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

| | |
|------------------------|--|
| CPU | • INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz) |
| Chipset | • INTEL®NM10 Express chipset |
| Memory | • 2 * DDR3 1067MHz Single CH SO-DIMM up to 4GB |
| Expansion Slots | • 1 * PCI slot • 1 * Mini PCI-E socket |
| Storage | • 2 * Serial ATA2 3Gb/s connectors |
| Audio | • Realtek ALC662 6-Channel HD Audio |
| Ethernet LAN | • 2 * RTL8111EVL PCI-E Gigabit LAN |
| LVDS | • Onboard 24-bits single channel connector |

| | |
|---------------------------|--|
| • USB | • Embedded 7 * USB 2.0/1.1 |
| • Special Features | • Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog |
| • Rear Panel I/O | • 4 * USB 2.0/1.1 ports • 2 * RJ-45 port • 3 * Audio I/O ports (Line-in, MIC and Line-out) • 1 * VGA port • 1 * HDMI port • 2 * COM ports (COM2 for RS232/422/485) • 1 * +12V DC-in jack |
| • Internal I/O | • 2 * USB 2.0/1.1 headers for 3 USB 2.0 ports • 1 * PS/2 Mouse & 1 * Keyboard header • 2 * NB / Chassis Fan connectors; • 1 * LVDS header/1 * Inverter header • 1 * AUDIO header • 4* RS232 headers |
| • BIOS | • AMI 16MB UEFI DIP Flash ROM |
| • Functional | • ATM, Automation, Medical Equipment, Kiosk, Networking, POS, General Application, Transportation |
| • Packing | • Color Box Dimension ■200(W) x 200(D) x 70(H)mm |
| • Certificate | • CE, FCC, RoHS |
| • Temperature | • Operating within 0~40 centigrade (Suggest to use system FAN) • Storage within -20-85 centigrade |
| • Form Factor | • Mini ITX Form Factor(17cmx17cm) |

Product Accessories

- 4x COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield